

Grundy County Land Use Department
Heidi Miller Director
E-Mail: hmiller@grundyco.org
Call: 815-941-3228
Fax: 815-941-3432
Hours Monday – Friday 8-4:30



POOL PERMIT

Name: _____ Date: _____

Address: _____ City _____

State _____ Zip Code _____ Phone # _____

Cell # _____ Cost of Improvement: _____

Contractor _____ Contact # _____

PIN Number of pool site: _____

Address of pool site: _____

Size of Pool: _____

Signature: _____ Signature: _____
(Owner) (Contractor)


FOR OFFICE USE ONLY

Issued by: _____ Date: _____

Permit # _____ Fee: _____

Receipt # _____ Check # _____ Date Received _____

PROVIDE PLAT OF SURVEY SHOWING THE LOCATION OR COMPLETE SITE PLAN SKETCH BELOW



REQUIREMENTS

- Pool shall be located 10' from side and rear property lines and 10' from the home.
- All ladders shall have capability of closing and locking
- All gates shall be self-closing and self-latching
- A temporary fence shall be provided while the site is under construction
- Pools shall be provided with one or more ring buoys not more than 15" in diameter with a 3/16" line 3' in length or longer.
- A Well & Septic clearance permit must be obtained from the Grundy County Health Department

INFORMATION FOR REVIEW

- Provide pool construction plans with detail of electric, plumbing, and concrete if applicable.
- Provide placement of pool with setbacks

INSPECTIONS:

- Plumbing Inspections
- Final inspection to check placement, fencing, general construction and electrical work.

SHOW FENCE PROTECTION

- Fence protection shall be 48" in height. Either a 48" fence enclosing the yard or a barrier construction on top of the pool that provides an overall barrier of 48". Above ground pools 48" in height at all point shall serve as its own barrier. The pool shall have a removable ladder.

- 3109.4.1.8 **DWELLING WALL HAS A BARRIER:** Where a wall of a dwelling serves as part of the barrier, one of the following shall apply:
 1. Doors with direct access to the pool through that wall shall be equipped with an alarm that produces an audible warning when the door and/or its screen, if present, are opened. The alarm shall be listed and labeled in accordance with UL 2017. In dwellings not required to be Accessible units, Type A units or Type B units, the deactivation switch shall be located 54 inches (1372 mm) or more above the threshold of the door. IN dwellings required to be Accessible units, Type A units or Type B units, the deactivation switch (es) shall be located at 54 inches (1372 mm) maximum and 48 inches (1219mm) minimum above the threshold of the door.
 2. The pool shall be equipped with a power safety cover that complies with ASTM F 1346.
 3. Other means of protection, such as self-closing doors with self-latching devices, which are *approved*, shall be accepted so long as the degree of protection afforded is not less than the protection afforded by Section 3109.4.1.8, Item 1 or 2.

AVOIDING CREATING A NUISANCE

- A poorly maintained swimming pool provides an ideal breeding ground for mosquitoes. According to Illinois Compiled Statute, it is a public health nuisance and a violation of Statute "to create a condition, through the improper maintenance of a swimming pool or wading pool, or by causing an action that alters the condition of a natural body of water, so that it harbors mosquitoes, flies, or other animal pests that are offensive, injurious, or dangerous to the health of individuals of the public." (720 ILCS 5/47-5,(16))

- If you are unable to care for your pool, please drain and cover tightly. If unable to do this please treat with chlorine, or mosquito larvicide. Larvicides can be purchased at most hardware stores or pool supply stores.